



xangati

Specification Sheet

	X500	X1000
Server	One Dual-Core CPU (2.66Ghz)	Two Dual-Core CPU (3.0Ghz)
Memory	4G	8G
	X500 and X1000	
Form Factor	2U chassis support for max. motherboard size – 13" x 13.68" E-ATX	
Processor Support	Dual Xeon 1333 MHz FSB Processors	
Dimensions	Height 3.5" (89mm) Width 16.8" (428mm) Depth 25.5" (648mm) Gross Weight 50 lbs (22.7kg) Available Colors Black	
Expansion Slots	7x low-profile full-length expansion slots	
Drive Bays	Hot-swap 8x 1" U320 SCSI Hot-swap drive trays	
SCSI Backplane	1x 2U Dual-Channel U320 SCSI backplane	
Peripheral Drives	DVD-ROM Slim 8x DVD, 24x CD, DVD-ROM Drive	
Front Panel	Buttons	Power On/Off button System Reset button
	LEDs	Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED Power fail LED
	Ports	2x USB Ports + DB9 COM Port (optional)
System Cooling	Fans 3x 80mm 6300 RPM fans	
System Monitoring	Chassis intrusion switch	
Operating Environment (System)	Operating Temperature Range	10 - 35°C (50° - 95°F)
	Non-Operating Temperature Range	-40 - 70°C (-40° - 158°F)
	Humidity Range	8 - 90% non-condensing
	Non-Operating Humidity Range	5 - 95% non-condensing
Power Supply	700W AC power supply w/ PFC	
	AC Voltage	100 - 240V, 60-50Hz, 10 - 4 Amp
	+5V standby	4 Amp
	+12V	57 Amp
	+5V	30 Amp
	+3.3V	24 Amp
	-12V	0.6 Amp
Regulatory (Power Supply)	Power Supply Safety / EMC	USA - UL listed
		Canada - CUL listed
		Germany - TUV Certified
		EN 60950/IEC 60950-Compliant
		CB Report
		CCC Certification